



**ENTERPRISES, INC.**

P. O. Box 28180 Panama City Beach, FL 32411  
Phone: 850-774-1742 Fax: 419-710-0521  
e-mail: [espinner@bfbenterprises.com](mailto:espinner@bfbenterprises.com)  
[www.bfbenterprises.com](http://www.bfbenterprises.com)

## PRODUCT DATA SHEET

### BFB C9 DP110

**BFB C9 DP110** is a dark aromatic thermoplastic resin that has a high level of compatibility with, and excellent resistance to, acids, alkalis and moisture. Its **major uses are in paints, printing inks, rubber compounds and tires**. It can also be used as a tackifier in hot-melt adhesives, as a water-repellent agent, concrete curing agent, and as an asphalt binder.

#### PRODUCT PROPERTIES

##### Specifications

Color, Gardner, 50% in toluene, max:	17
Softening Point, Ring & Ball, °C:	100-110
Acid Value (mg KOH/g), max:	0.1
Volatile Content, weight %, max:	1.0
Bromine Number, Br cg/g, max:	85
Molecular Weight (Mw):	1350-1950

#### FEATURES

Dark yellow to brown color. Excellent compatibility with EVA and synthetic rubbers. Good resistance to acid, alkalis and moisture. Good initial adhesion and cohesion.

#### SUGGESTED APPLICATIONS

Paints, printing inks, adhesives, rubber compounds, tires.

#### AVAILABLE FORMS/PACKAGING

Lump or flake; net 25kg paper bag or woven-plastic big bags at 500kg, 600kg, or 750kg.

#### SAFETY INFORMATION

Please refer to the **Material Safety Data Sheet**. Non-hazardous.