

P. O. Box 28180 Panama City Beach, FL 32411 Phone: 850-774-1742 Fax: 419-710-0521 e-mail: espinner@bfbenterprises.com www.bfbenterprises.com

PRODUCT DATA SHEET

BFB C5-C9 C100

BFB C5-C9 C100 is a pale yellow catalytically copolymerized aliphatic-aromatic resin. Because of its tackiness and adhesive & cohesive strengths, it is an excellent tackifier for pressure sensitive adhesives. It is also used as a binder in rubber compounds, paints, printing inks, & can also be used as a concrete curing agent & a binder in asphalt.

PRODUCT PROPERTIES

Specifications

Color, Gardner, 50% in toluene, max:

Softening Point, Ring & Ball, °C:

Acid Value (mg KOH/g), max:

Volatile Content, weight %, max:

Bromine Number, Br cg/g, max:

Specific Gravity, ASTM D71:

5
90-100
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-100
1.0
90-1

FEATURES

Pale yellow color. Excellent compatibility with EVA and synthetic rubbers. Good resistance to acid, alkalies and moisture. Low molecular weight and low volatility. Good initial adhesion and cohesion.

SUGGESTED APPLICATIONS

Pressure sensitive adhesives, paints, printing inks, rubber compounds, tires.

AVAILABLE FORMS/PACKAGING

Lump or flake net 25kg plastic bags or woven-plastic big bags at 500kg, 600kg, or 750kg.

SAFETY INFORMATON

Please refer to the Material Safety Data Sheet. Non-hazardous.